



Transmit



Receive



Decode



Control

Mini Transmitter RT20 BaseWave

The Mini Transmitter RT20 is both, a 3- and 4-channel transmitter. Every transmitter is delivered with a unique code.

More than 70 million alternative codes ensure the uniqueness of every code.

The code can be transferred to any number of other transmitters simply at the push of a button, just as easy as duplicating a key.

The visor clip, which has to be fitted to the mounting plate, enables attaching the Mini Transmitter to the sun visor of a car.



RT20-XX0XM-01

Technical Details

Coding	factory coding with over 70 million options, code duplication by the user is possible
Channels	3 or 4 (3 or 4 buttons)
Range	up to 150 m under favourable open field conditions
Power Supply	1x 3V battery, CR2032
Operation Indicator	LED
Control	transmission lasts for as long as button is pressed (but max. 36 s)
Degree of Protection	IP54
Operating Temperature	-20 °C to +60 °C
Dimensions	40 x 70 x 17 mm
Weight	25 g (including battery)

Accessories



RT20-ACC-01



RT20-ACC-02



ACC-CON-01

Scope of Delivery

- Mini Transmitter incl. battery
- Mounting Plate
- Programming Connector
- Operating Manual

Accessories (optional)

- Visor Clip
- Mounting Plate
- Programming Connector
- Battery

Models

Product Key	Description	Frequency
on request	Mini Transmitter 3-Channel	315.00 MHz
on request	Mini Transmitter 4-Channel	315.00 MHz
RT20-4103M-01	Mini Transmitter 3-Channel	433.92 MHz
RT20-4104M-01	Mini Transmitter 4-Channel	433.92 MHz
RT20-5003M-01	Mini Transmitter 3-Channel	868.30 MHz
RT20-5004M-01	Mini Transmitter 4-Channel	868.30 MHz
on request	Mini Transmitter	916.50 MHz
RT20-ACC-01	Mounting Plate	
RT20-ACC-02	Visor Clip	
ACC-CON-01	Programming Connector	
ACC-BAT-05	Battery CR2032	