

CNY17F-1X, CNY17F-2X, CNY17F-3X, CNY17F-4X
 CNY17F-1, CNY17F-2, CNY17F-3, CNY17F-4



ISOCOM
 COMPONENTS

**NON-BASE LEAD
 OPTICALLY COUPLED ISOLATOR
 PHOTOTRANSISTOR OUTPUT**



APPROVALS

- UL recognised, File No. E91231
 Package Code GG
- 'X' SPECIFICATION APPROVALS
 - VDE 0884 in 3 available lead forms : -
 - STD
 - G form
 - SMD approved to CECC 00802
 - Certified to EN60950 by
 Nemko - Certificate No. P01102464

DESCRIPTION


The CNY17F-1, CNY17F-2, CNY17F-3, CNY17F-4 series of optically coupled isolators consist of infrared light emitting diode and NPN silicon photo transistor in a standard 6 pin dual in line plastic package with the base pin unconnected.

FEATURES

- Options :-
 10mm lead spread - add G after part no.
 Surface mount - add SM after part no.
 Tape & reel - add SMT&R after part no.
- High BV_{CEO} (70V min)
- High Isolation Voltage ($5.3kV_{RMS}$, $7.5kV_{PK}$)
- Base pin unconnected for improved noise immunity in high EMI environment

APPLICATIONS

- DC motor controllers
- Industrial systems controllers
- Signal transmission between systems of different potentials and impedances



**ABSOLUTE MAXIMUM RATINGS
 (25°C unless otherwise specified)**

Storage Temperature _____ -55°C to +150°C
 Operating Temperature _____ -55°C to +100°C
 Lead Soldering Temperature
 (1/16 inch (1.6mm) from case for 10 secs) 260°C

INPUT DIODE

Forward Current _____ 60mA
 Reverse Voltage _____ 6V
 Power Dissipation _____ 105mW


OUTPUT TRANSISTOR

Collector-emitter Voltage BV_{CEO} _____ 70V
 Emitter-collector Voltage BV_{ECO} _____ 6V
 Collector Current _____ 50mA
 Power Dissipation _____ 160mW


POWER DISSIPATION

Total Power Dissipation _____ 200mW
 (derate linearly 2.67mW/°C above 25°C)

**OPTION SM
 SURFACE MOUNT**



OPTION G



ISOCOM COMPONENTS LTD

Unit 25B, Park View Road West,
 Park View Industrial Estate, Brenda Road
 Hartlepool, TS25 1UD England Tel:
 (01429)863609 Fax: (01429)863581 e-mail
 sales@isocom.co.uk http://www.isocom.com

ELECTRICAL CHARACTERISTICS (T_A = 25°C Unless otherwise noted)

| PARAMETER | | MIN | TYP | MAX | UNITS | TEST CONDITION |
|--|--|------|-----|-----------------|---------------------------------|--|
| Input | Forward Voltage (V _F) | | 1.2 | 1.65 | V | I _F = 60mA |
| | Reverse Current (I _R) | | | 10 | μA | V _R = 6V |
| Output | Collector-emitter Breakdown (BV _{CEO}) (note 2) | 70 | | | V | I _C = 1mA |
| | Emitter-collector Breakdown (BV _{ECO}) | 6 | | | V | I _E = 100μA |
| | Collector-emitter Dark Current (I _{CEO}) | | | 50 | nA | V _{CE} = 10V |
| Coupled | Current Transfer Ratio (CTR) (Note 2) | | | | | |
| | CNY17F-1 | 40 | 80 | | % | 10mA I _F , 5V V _{CE} |
| | CNY17F-2 | 63 | 125 | | % | 10mA I _F , 5V V _{CE} |
| | CNY17F-3 | 100 | 200 | | % | 10mA I _F , 5V V _{CE} |
| | CNY17F-4 | 160 | 320 | | % | 10mA I _F , 5V V _{CE} |
| | Collector-emitter Saturation Voltage V _{CE(SAT)} | | | 0.4 | V | 10mA I _F , 2.5mA I _C |
| | Input to Output Isolation Voltage V _{ISO} | 5300 | | | V _{RMS} | See note 1 |
| | 7500 | | | V _{PK} | See note 1 | |
| Input-output Isolation Resistance R _{ISO} | 5x10 ¹⁰ | | | Ω | V _{IO} = 500V (note 1) | |

Note 1 Measured with input leads shorted together and output leads shorted together.

Note 2 Special Selections are available on request. Please consult the factory.

TYPICAL SWITCHING CHARACTERISTICS

1. Linear Operation (without saturation) Fig 1.
I_F = 10mA, V_{CC} = 5V, R_L = 75Ω

| | | | UNITS |
|-------------------|------------------|-----|-------|
| Turn-on Time | t _{on} | 3.0 | μs |
| Rise Time | t _r | 2.0 | μs |
| Turn-off Time | t _{off} | 2.3 | μs |
| Fall Time | t _f | 2.0 | μs |
| Cut-off Frequency | F _{CO} | 250 | kHz |





FIG 1


FIG 2

2. Switching Operation (with saturation) Fig 2
V_{CC} = 5V, R_L = 1kΩ


| GROUP | -1 (I _F =20mA) | -2 and -3 (I _F =10mA) | -4 (I _F =5mA) | UNITS | |
|--------------------|------------------------------|-------------------------------------|-----------------------------|-------|----|
| Turn-on Time | t _{on} | 3.0 | 4.2 | 6.0 | μs |
| Rise Time | t _r | 2.0 | 3.0 | 4.6 | μs |
| Turn-off Time | t _{off} | 18 | 23 | 25 | μs |
| Fall Time | t _f | 11 | 14 | 15 | μs |
| V _{CESAT} | | | | ≤ 0.4 | V |




Collector Power Dissipation vs. Ambient Temperature




Collector Current vs. Collector-emitter Voltage (normalised to CNY17F-3)




Forward Current vs. Ambient Temperature



Current Transfer Ratio vs. Forward Current



Relative Current Transfer Ratio vs. Ambient Temperature



Collector-emitter Saturation Voltage vs. Ambient Temperature

