


AUDIO Capacitor



Rated capacitance μF	Capacitance tolerance %	Dimensions	
		D max. mm	L+3/-2 mm
0,022	±2% / ±5%	12,7	29
0,027		13,7	
0,033		14,9	
0,039		16,0	
0,047		17,3	
0,056		18,7	
0,068		13,5	
0,082		14,5	
0,1		15,8	
0,12		17,1	
0,15		18,8	
0,18		20,4	
0,22		22,3	
0,27		24,6	38
0,33		27,0	
0,39		29,1	
0,47		31,8	
0,56		25,3	
0,68		27,6	
0,82		30,2	60
1,0		35,9	

Dane Techniczne / Technical data:

Napięcie znamionowe Ur 600VDC
Rated voltage

Tg kąta stratności <0,0050 @ 1kHz dla C≤1μF
Dissipation factor <0,0080 @ 1kHz dla C>1μF

Kategoria klimatyczna 025/085/21/C
Climatic category

Wymiary Dimensions zgodnie z tabelą
Dimensions acc. to table

Other capacitance values, lengths and types of leads are available at request upon prior agreement.

Description:


The KFPM-01 capacitors are distinguished by the use of electrodes made of copper foil, separated by polypropylene film. These capacitors are designed for use in audio equipment. The design of the capacitors minimizes the parasitic impedance components: inductance and resistance, resulting in improved quality of sound in a given audio system, where the positive effect is enhanced by the use of electrodes made of copper foil.

High quality and durability of the capacitors is assured by the use of carefully selected materials, production technology, as well as testing and measuring methods. These capacitors feature the use of axial terminals made of tinned copper wire, cover in the form of special protective tape, and self-extinguishing potting compound of flammability class V0.

The capacitors are furthermore subjected to a series of specific tests and measurements, including a unique test using pulses of increased current amplitude and frequency of 22kHz.

The KFPM-01 capacitors can be used in d.c. and a.c. circuits within the temperature range of their climatic category. The d.c. voltage value or a.c. voltage amplitude should not exceed the specified rated voltage.

PRINTING LAYOUT EXAMPLE



 **MIFLEX SA**

ZAKŁADY PODZESPOŁÓW RADIOSYNTETYCZNYCH
99-300 KUTNO, ul.GRUNWALDZKA 3
Telefon: +48 24 355 11 00
Fax: +48 24 355 11 88
e-mail: miflexsa@miflex.com.pl

Index: KFPM...

Revision date
18.06.2020

Page
1/1