

NCV8405A, NCV8405B

Self-Protected Low Side Driver with Temperature and Current Limit

NCV8405A/B is a three terminal protected Low-Side Smart Discrete device. The protection features include overcurrent, overtemperature, ESD and integrated Drain-to-Gate clamping for overvoltage protection. This device is suitable for harsh automotive environments.

Features

- Short-Circuit Protection
- Thermal Shutdown with Automatic Restart
- Overvoltage Protection
- Integrated Clamp for Inductive Switching
- ESD Protection
- dV/dt Robustness
- Analog Drive Capability (Logic Level Input)
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

Typical Applications

- Switch a Variety of Resistive, Inductive and Capacitive Loads
- Can Replace Electromechanical Relays and Discrete Circuits
- Automotive / Industrial




ON Semiconductor®


www.onsemi.com

V _{(BR)DSS} (Clamped)	R _{DS(ON)} TYP	I _D MAX
42 V	90 mΩ @ 10 V	6.0 A*

*Max current limit value is dependent on input condition.



MARKING DIAGRAM



A = Assembly Location

Y = Year

W, WW = Work Week

xxxxx = 8405A or 8405B

G or • = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 10 of this data sheet.

NCV8405A, NCV8405B

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Drain-to-Source Voltage Internally Clamped	V_{DSS}	42	V
Drain-to-Gate Voltage Internally Clamped ($R_G = 1.0 \text{ M}\Omega$)	V_{DGR}	42	V
Gate-to-Source Voltage	V_{GS}	± 14	V
Continuous Drain Current	I_D	Internally Limited	
Power Dissipation – SOT-223 Version @ $T_A = 25^\circ\text{C}$ (Note 1) @ $T_A = 25^\circ\text{C}$ (Note 2) @ $T_S = 25^\circ\text{C}$	P_D	1.0 1.7 11.4	W
Power Dissipation – DPAK Version @ $T_A = 25^\circ\text{C}$ (Note 1) @ $T_A = 25^\circ\text{C}$ (Note 2) @ $T_S = 25^\circ\text{C}$		2.0 2.5 40	
Thermal Resistance – SOT-223 Version Junction-to-Ambient Steady State (Note 1) Junction-to-Ambient Steady State (Note 2) Junction-to-Soldering Point Steady State	$R_{\theta JA}$ $R_{\theta JA}$ $R_{\theta JS}$	130 72 11	$^\circ\text{C}/\text{W}$
Thermal Resistance – DPAK Version Junction-to-Ambient Steady State (Note 1) Junction-to-Ambient Steady State (Note 2) Junction-to-Soldering Point Steady State	$R_{\theta JA}$ $R_{\theta JA}$ $R_{\theta JS}$	60 50 3.0	
Single Pulse Drain-to-Source Avalanche Energy ($V_{DD} = 40 \text{ V}$, $V_G = 5.0 \text{ V}$, $I_{PK} = 2.8 \text{ A}$, $L = 80 \text{ mH}$, $R_{G(ext)} = 25 \Omega$, $T_J = 25^\circ\text{C}$)	E_{AS}	275	mJ
Load Dump Voltage $V_{LD} = V_A + V_S$ ($V_{GS} = 0$ and 10 V , $R_I = 2.0 \Omega$, $R_L = 6.0 \Omega$, $t_d = 400 \text{ ms}$)	V_{LD}	53	V
Operating Junction Temperature	T_J	-40 to 150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to 150	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Surface-mounted onto min pad FR4 PCB, (2 oz. Cu, 0.06" thick).
2. Surface-mounted onto 2" sq. FR4 board (1" sq., 1 oz. Cu, 0.06" thick).




Figure 1. Voltage and Current Convention

NCV8405A, NCV8405B

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Test Condition	Symbol	Min	Typ	Max	Unit
-----------	----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Drain-to-Source Breakdown Voltage (Note 3)	$V_{GS} = 0 \text{ V}, I_D = 10 \text{ mA}, T_J = 25^\circ\text{C}$	$V_{(BR)DSS}$	42	46	51	V	
	$V_{GS} = 0 \text{ V}, I_D = 10 \text{ mA}, T_J = 150^\circ\text{C}$ (Note 5)		42	45	51		
Zero Gate Voltage Drain Current	$V_{GS} = 0 \text{ V}, V_{DS} = 32 \text{ V}, T_J = 25^\circ\text{C}$	I_{DSS}		0.5	2.0	μA	
	$V_{GS} = 0 \text{ V}, V_{DS} = 32 \text{ V}, T_J = 150^\circ\text{C}$ (Note 5)			2.0	10		
Gate Input Current	$V_{DS} = 0 \text{ V}, V_{GS} = 5.0 \text{ V}$		I_{GSSF}		50	100	μA

ON CHARACTERISTICS (Note 3)

Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 150 \mu\text{A}$	$V_{GS(\text{th})}$	1.0	1.6	2.0	V
Gate Threshold Temperature Coefficient		$V_{GS(\text{th})}/T_J$		4.0		$-\text{mV/}^\circ\text{C}$
Static Drain-to-Source On-Resistance	$V_{GS} = 10 \text{ V}, I_D = 1.4 \text{ A}, T_J = 25^\circ\text{C}$	$R_{DS(\text{on})}$		90	100	$\text{m}\Omega$
	$V_{GS} = 10 \text{ V}, I_D = 1.4 \text{ A}, T_J = 150^\circ\text{C}$ (Note 5)			165	190	
	$V_{GS} = 5.0 \text{ V}, I_D = 1.4 \text{ A}, T_J = 25^\circ\text{C}$			105	120	
	$V_{GS} = 5.0 \text{ V}, I_D = 1.4 \text{ A}, T_J = 150^\circ\text{C}$ (Note 5)			185	210	
	$V_{GS} = 5.0 \text{ V}, I_D = 0.5 \text{ A}, T_J = 25^\circ\text{C}$			105	120	
	$V_{GS} = 5.0 \text{ V}, I_D = 0.5 \text{ A}, T_J = 150^\circ\text{C}$ (Note 5)			185	210	
Source-Drain Forward On Voltage	$V_{GS} = 0 \text{ V}, I_S = 7.0 \text{ A}$	V_{SD}		1.05		V

SWITCHING CHARACTERISTICS (Note 5)

Turn-ON Time (10% V_{IN} to 90% I_D)	$V_{GS} = 10 \text{ V}, V_{DD} = 12 \text{ V}$ $I_D = 2.5 \text{ A}, R_L = 4.7 \Omega$	t_{ON}		20		μs
Turn-OFF Time (90% V_{IN} to 10% I_D)		t_{OFF}		110		
Slew-Rate ON (70% V_{DS} to 50% V_{DS})	$V_{GS} = 10 \text{ V}, V_{DD} = 12 \text{ V},$ $R_L = 4.7 \Omega$	$-dV_{DS}/dt_{ON}$		1.0		$\text{V}/\mu\text{s}$
Slew-Rate OFF (50% V_{DS} to 70% V_{DS})		dV_{DS}/dt_{OFF}		0.4		

SELF PROTECTION CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted) (Note 4)

Current Limit	$V_{DS} = 10 \text{ V}, V_{GS} = 5.0 \text{ V}, T_J = 25^\circ\text{C}$	I_{LIM}	6.0	9.0	11	A
	$V_{DS} = 10 \text{ V}, V_{GS} = 5.0 \text{ V}, T_J = 150^\circ\text{C}$ (Note 5)		3.0	5.0	8.0	
	$V_{DS} = 10 \text{ V}, V_{GS} = 10 \text{ V}, T_J = 25^\circ\text{C}$		7.0	10.5	13	
	$V_{DS} = 10 \text{ V}, V_{GS} = 10 \text{ V}, T_J = 150^\circ\text{C}$ (Note 5)		4.0	7.5	10	
Temperature Limit (Turn-off)	$V_{GS} = 5.0 \text{ V}$ (Note 5)	$T_{LIM(off)}$	150	180	200	$^\circ\text{C}$
Thermal Hysteresis	$V_{GS} = 5.0 \text{ V}$	$\Delta T_{LIM(on)}$		15		
Temperature Limit (Turn-off)	$V_{GS} = 10 \text{ V}$ (Note 5)	$T_{LIM(off)}$	150	165	185	
Thermal Hysteresis	$V_{GS} = 10 \text{ V}$	$\Delta T_{LIM(on)}$		15		

GATE INPUT CHARACTERISTICS (Note 5)

Device ON Gate Input Current	$V_{GS} = 5 \text{ V}, I_D = 1.0 \text{ A}$	I_{GON}		50		μA
	$V_{GS} = 10 \text{ V}, I_D = 1.0 \text{ A}$			400		
Current Limit Gate Input Current	$V_{GS} = 5 \text{ V}, V_{DS} = 10 \text{ V}$	I_{GCL}		0.05		mA
	$V_{GS} = 10 \text{ V}, V_{DS} = 10 \text{ V}$			0.4		
Thermal Limit Fault Gate Input Current	$V_{GS} = 5 \text{ V}, V_{DS} = 10 \text{ V}$	I_{GTL}		0.22		mA
	$V_{GS} = 10 \text{ V}, V_{DS} = 10 \text{ V}$			1.0		

ESD ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted) (Note 5)

Electro-Static Discharge Capability	Human Body Model (HBM)	ESD	4000			V
	Machine Model (MM)		400			

- 3. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2\%$.
- 4. Fault conditions are viewed as beyond the normal operating range of the part.
- 5. Not subject to production testing.

NCV8405A, NCV8405B

TYPICAL PERFORMANCE CURVES




Figure 2. Single Pulse Maximum Switch-off Current vs. Load Inductance




Figure 3. Single Pulse Maximum Switching Energy vs. Load Inductance




Figure 4. Single Pulse Maximum Inductive Switch-off Current vs. Time in Clamp




Figure 5. Single Pulse Maximum Inductive Switching Energy vs. Time in Clamp




Figure 6. Output Characteristics




Figure 7. Transfer Characteristics

NCV8405A, NCV8405B

TYPICAL PERFORMANCE CURVES




Figure 8. $R_{DS(on)}$ vs. Gate-Source Voltage




Figure 9. $R_{DS(on)}$ vs. Drain Current




Figure 10. Normalized $R_{DS(on)}$ vs. Temperature




Figure 11. Current Limit vs. Gate-Source Voltage




Figure 12. Current Limit vs. Junction Temperature




Figure 13. Drain-to-Source Leakage Current

TYPICAL PERFORMANCE CURVES




Figure 14. Normalized Threshold Voltage vs.
Temperature




Figure 15. Body-Diode Forward
Characteristics




Figure 16. Resistive Load Switching Time vs.
Gate-Source Voltage




Figure 17. Resistive Load Switching
Drain-Source Voltage Slope vs. Gate-Source
Voltage




Figure 18. Resistive Load Switching Time vs.
Gate Resistance




Figure 19. Drain-Source Voltage Slope during
Turn On and Turn Off vs. Gate Resistance

NCV8405A, NCV8405B

TYPICAL PERFORMANCE CURVES




Figure 20. Transient Thermal Resistance




Figure 21. θ_{JA} vs. Copper

NCV8405A, NCV8405B

TEST CIRCUITS AND WAVEFORMS




Figure 22. Resistive Load Switching Test Circuit




Figure 23. Resistive Load Switching Waveforms

NCV8405A, NCV8405B

TEST CIRCUITS AND WAVEFORMS




Figure 24. Inductive Load Switching Test Circuit




Figure 25. Inductive Load Switching Waveforms

NCV8405A, NCV8405B


ORDERING INFORMATION

Device	Package	Shipping [†]
NCV8405ASTT1G	SOT-223 (Pb-Free)	1000 / Tape & Reel
NCV8405ASTT3G	SOT-223 (Pb-Free)	4000 / Tape & Reel
NCV8405ADTRKG	DPAK (Pb-Free)	2500 / Tape & Reel
NCV8405BDTRKG	DPAK (Pb-Free)	2500 / Tape & Reel

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS

onsemi




TOP VIEW

DPAK (SINGLE GAUGE)
CASE 369C
ISSUE G


DATE 31 MAY 2023

NOTES:


1. DIMENSIONING AND TOLERANCING ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3, AND Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.
7. OPTIONAL MOLD FEATURE.





SIDE VIEW



BOTTOM VIEW




BOTTOM VIEW



DETAIL A
ROTATED 90° CW

DIM	INCHES		MILLIMETERS	
	MIN.	MAX.	MIN.	MAX.
A	0.086	0.094	2.18	2.38
A1	0.000	0.005	0.00	0.13
b	0.025	0.035	0.63	0.89
b2	0.028	0.045	0.72	1.14
b3	0.180	0.215	4.57	5.46
c	0.018	0.024	0.46	0.61
c2	0.018	0.024	0.46	0.61
D	0.235	0.245	5.97	6.22
E	0.250	0.265	6.35	6.73
e	0.090	BSC	2.29	BSC
H	0.370	0.410	9.40	10.41
L	0.055	0.070	1.40	1.78
L1	0.114	REF	2.90	REF
L2	0.020	BSC	0.51	BSC
L3	0.035	0.050	0.89	1.27
L4	----	0.040	----	1.01
Z	0.155	----	3.93	----

**GENERIC
MARKING DIAGRAM***



IC

Discrete

- XXXXXX = Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
WW = Work Week
G = Pb-Free Package

RECOMMENDED MOUNTING FOOTPRINT*

*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES MANUAL, SOLDERRM/D.

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. Emitter
4. COLLECTOR

STYLE 2:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

STYLE 3:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. CATHODE

STYLE 4:
PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

STYLE 5:
PIN 1. GATE
2. ANODE
3. CATHODE
4. ANODE

STYLE 6:
PIN 1. MT1
2. MT2
3. GATE
4. MT2

STYLE 7:
PIN 1. GATE
2. COLLECTOR
3. Emitter
4. COLLECTOR

STYLE 8:
PIN 1. N/C
2. CATHODE
3. ANODE
4. CATHODE

STYLE 9:
PIN 1. ANODE
2. CATHODE
3. RESISTOR ADJUST
4. CATHODE

STYLE 10:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. ANODE

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "■", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON10527D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	DPAK (SINGLE GAUGE)	PAGE 1 OF 1

onsemi and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, **ONSEMI**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi's** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales

